

# Raci Spacer Options: **Medium**

<b>Type M, N</b> 18, 25, 36, 41, 50, 75, 90 mm				<b>Type P, Q</b> 110, 120 mm	
O.D. range inches		O.D. range mm		No. of elements to make a ring	
min	max	min	max	M/P	N/Q
5.63	6.61	143	168	1	1
6.65	7.91	169	201	2	-
7.95	8.94	202	227	1	2
8.98	9.92	228	252	2	1
9.96	11.26	253	286	3	-
11.30	12.24	287	311	2	2
12.28	13.27	312	337	3	1
13.31	15.55	338	395	4	-
15.59	16.57	396	421	4	1
16.61	19.88	422	505	5	-
19.92	23.23	506	590	6	-
23.27	26.54	591	674	7	-
26.57	29.88	675	759	8	-
29.92	36.02	760	915	9	-
33.46	39.96	850	1015	10	-
Elements	Runner Height In.	Max Load Per Ring			
		Lbs		Kg	
M/N 18	0.70			2425	1100
M/N 25	0.98			2535	1150
M/N 36	1.42			4400	2000
M 41	1.61			3968	1800
M/N 50	1.97			3638	1650
M/N 75	2.95			4300	1950
M/N 90	3.54			3858	1750
P/Q 110	4.33			2315	1050
P/Q 120	4.72			2200	1000